

AL-HU01



AXCELL Robot batteries are compatible battery types built as per OE specifications. Available in different technologies (NiMH, Li-Ion or LiFePo4), these batteries are designed for intensive charge & discharge and developed with first-class safety features. Ideal to offer the robot great autonomy in working!

BENEFITS

- > **Compatible battery type**
Matching with OE specifications
- > **High cycle life**
High quality lithium cells
- > **Low self-discharge**
Long shelf life & ideal for seasonal use
- > **Multi-position mounting**
Even upside down
- > **Covers the majority of parc**
More than 200 robots models covered
- > **Comes with first-class safety features**
BMS integrated

COMPATIBILITY LIST (NOT EXHAUSTIVE)

- > **HUSQVARNA**
Automower 105/305/308
- > **GARDENA**
R38Li / R40Li / R45Li...

SPECIFICATIONS

VOLTAGE:

18V

CAPACITY:

2AH

POWER:

36WH

PROTECTIONS FUNCTION (PCM):

OPERATING TEMPERATURE

Charge temperature: 0°C to 45°C

Discharge temperature: -10°C to 60°C

Storage temperature: 0°C to 40°C

DIMENSIONS & WEIGHT

Length (L): 70.5mm ±2mm

Width (W): 66mm ±2mm

Height (H): 57mm ±2mm

Weight: 0,25Kg

TERMINAL

